



## Pro Series - Long Range Face Recognition

# Realtime Pro 1400A



Long Range  
Face Recognition



Live Face  
Detection



Touch Screen



4.5" LCD



Wifi



Cloud  
Connectivity



Infrared  
Detection

## Specifications

» Face capacity	10000
» Card Capacity	10000
» Attendance Log	300,000
» Light Sensitivity	15000 Lux
» LED	LED Double high power infrared light
» Display	4.7" Capacitive LCD touch Screen
» Communication	TCP/IP, 1xUSB Disk, WIFI, GPRS (Optional)
» Power Supply	DC 12V, 2A
» Operating temperature	-15°C ~ +60°C
» Processor Speed	1GHz
» RAM	1GB
» Storage	8GB
» Screen Resolution	1280x720
» Enclosure Class	Ip55
» Front Camera	2MP
» Operating System	LINUX
» Identification Style	Dynamic Facial, PIN, Face & PIN Combination
» Identification Mode	1:1, 1:N
» Identification Time	<0.1S
» Detection Range	8 Feet
» Wiegand	Wiegand In and Wiegand Out
» Dimension	185mm*110mm*20mm
» Face Recognition Technology	In Built Standalone Device
» Face Liveness Detection	Yes
» Battery Backup	Optional
» Industrial Grade Face Reader	Yes
» Suitability For Outdoor Installation	Yes
» Storage Expand ability	Micro SD Card
» Reader Configuration	Configured IN and Out mode base Specified time
» Encryption	128
» Enrolment Time	<30 seconds
» Data Display	Capture Photo, Employee No, Mode of attendance (IN/OUT), Date, Time, Status of recognition.
» False Acceptance Rate (FAR)	>0.01%
» False Rejection Rate	≤ 1%
» Partial Facial	Yes